

HEAT KING

HK 300 MOBILE GLYCOL HEATING SYSTEM



FEATURES

- 4-700FT HOSES
- THAW UP TO 5,600 FT²
- CURE UP TO 11,200 FT²
- TEMPORARY HEAT UP TO 12,000 FT²
- UP TO 120 HRS RUN TIME
- CSA/UL CERTIFIED
- PLC CONTROLLED SYSTEM
- BI-DIRECTIONAL POWERED REEL WITH FREEWHEEL FEATURE
- ON BOARD AIR COMPRESSOR

WWW.HEAT-KING.CA





DOUBLE LOOP TECHNOLOGY

By using shorter hoses, more fluid, and higher efficiency pumps with increased flow, the Heat King provides more consistent temperature to the field for better concrete curing and ground thawing results.



AVAILABLE IN PROPANE/NATURAL GAS

The HK 300 is now available in Propane and Natural Gas set-ups. These clean burning fuels are even more reliable than the legendary oil fired Heat King Systems. Because of their quiet operation they are perfectly suited for residential applications. For even more versatility the burner assemblies can be quickly changed from one to the other.

HK300 SPECIFICATIONS

<ul style="list-style-type: none"> • Hose • Hose • Supply Manifold • Return Manifold • Ground Thawing Capacity • Concrete Curing Capacity • Temporary Heating Capacity • Field Pump • Circulating Pump • Fuel Tank • Run Time • Fuel Consumption • Flo Indicator 	<ul style="list-style-type: none"> 4 - 700 ft Field Hoses (5/8" Hose) Unspool with one person 4 - 1/2" quick connect & 1 - 1 1/4" Camlock 4 - 1/2" quick connect & 1 - 1 1/4" Camlock up to 5,600 ft² up to 11,200 ft² 12,000 ft² (Varies with R-Value) 1 Hp Centrifugal 1/2 Hp Centrifugal 192 US GAL Up to 120 Hours HK 300 = 2.24 GPH, Genset = .55 GPH Ensures proper operation 	<ul style="list-style-type: none"> • Interior Lights • Mud Tray • Heater Capacity Diesel • Heater Capacity LP/NG • Glycol Tank • Electrical Requirements • Generator (Optional) • LP/NG Units (Optional) • Axle • Hitch • Dimensions • Weight (Fuel Empty/Full) • Burner 	<ul style="list-style-type: none"> Standard for ease of night operation Added under the reel to catch mud debris 311,000 BTU/H Heating Fuel Input 300,000 BTU/H (LP) 300,000 BTU/H (NG) 96 US GAL 2 - 120V AC 20A Circuits 1 - 7,000W 60 gallon Fuel Tank for Generator 1 - 7,000lb Torsion Axle, Electric Brakes 2 5/16" Ball (Pintle also available) 14'x86"x83" 6505 lbs / 7835 lbs Beckett Burner
---	---	---	--